



altro

Designed for possibilities.
Made for people.

Altro Walkway™ 20 product datasheet

Multi-purpose slip-resistant flooring in modern and traditional looks

Altro Walkway 20

Altro Walkway 20 is our hugely popular hard-wearing 2mm slip-resistant flooring. The range shares its palette with Altro XpressLay. This enables you to combine both ranges when you need traditionally-adhered and adhesive-free flooring in adjacent areas while maintaining a consistent look.

What's even better is Altro Walkway 20 offers you two distinct looks; traditional and modern. Both looks come with Altro Easyclean technology for superior cleanability and stain resistance.

A static-dissipative version is available, specifically designed for locations where static buildup must be avoided.

Altro Walkway 20 also looks great when paired with Altro XpressLay, Altro Aquarius, Altro Wood, Altro Orchestra or even Altro Zodiac Smooth.

Typical applications

General purpose

Features + benefits

- Hard-wearing 2mm slip-resistant flooring
- Shares palette with Altro XpressLay, allows coordination between traditionally adhered and adhesive-free slip-resistant flooring
- Matches colors with Altro Aquarius, allowing for seamless coordination from wet rooms to general areas.
- Static dissipative version available
- Achieves R10 slip resistance rating and SCoF of .78 dry, .80 wet
- FloorScore Certified / Low VOCs

Slip resistance

.78D
.80W

.66
DCOF

R10

Pendulum test
PTV
≥36

It is designers, specifiers and end-users' responsibility to ensure flooring is fit for purpose, and it's part of our role here at Altro to help make this process easy. Our flooring is separated into three categories: safety, slip-resistant and smooth.

Altro Walkway 20 is a slip-resistant flooring. It's a perfect choice for many commercial areas in which your slip risk is not as high as a commercial kitchen or other wet environments, but your patrons, patients, students and employees still deserve to be secure on their feet. Slip-resistant flooring from Altro will reduce the risk of slips, give you peace of mind and look good doing so.



Altro Easyclean

Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products' slip-resistant properties to shine through.


Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention







Cromwell Vets chose Altro Walkway 20.




Swan VMI2012P
WR291 / A1M01 LRV 75




Winter VMI2053
WR105 / A1M01 LRV 61




Blizzard VMI2055
WR79 / A1M191 LRV 44




Streetlight VMI2005P
WR287 / A1M79 LRV 45




Cloud VM2014
WR79 / A1M191 LRV 41



Temple VMI2009P
WR261 / A1M81 LRV 27




Rock VMI2004P
WR84 / A1M84 LRV 23




Fog VM20153
WR81 / A1M81 LRV 27


Fog available in static dissipative through special order.
VM20153SD




Dolphin VM2010
WR86 / A1M86 LRV 21




Whale VMI2054
WR86 / A1M86 LRV 20



Nickel VMI2019P
WR81 / A1M81 LRV 29




Pavement VMI2007P
WR83 / A1M83 LRV 14



Runway VMI2006P
WR72 / A1M72 LRV 9




Midnight VMI20421
WR72 / A1M72 LRV 11




Nightfall VMI2056
WR72 / A1M72 LRV 10




Black VMI20892
WR100 / A1M100 LRV 6



Coal VMI2058
WR100 / A1M100 LRV 6




Tarragon VMI2052
WR52 / A1M52 LRV 26




Skyline VM20332
WR52 / A1M52 LRV 24




Minster VM2018P
WR289 / A1M265 LRV 40




Bisque VMI2021P
WR364 / A1M335 LRV 50




Sand VMI2051
WR20 / A1M20 LRV 40




Tan VMI2018P
WR362 / A1M20 LRV 41




Rodeo VMI2020P
WR363 / A1M265 LRV 37




Bone VMI20215
WR20 / A1M20 LRV 37




Biscuit VMI20907
WR146 / A1M20 LRV 30




Tundra VMI20910
WR153 / A1M239 LRV 17




Savannah VMI2050
WR153 / A1M239 LRV 19




Tango VMI2031
WR42 / A1M42 LRV 14




Lupin VMI2059
WR286 / A1M286 LRV 17



Blue VMI20412
WR71 / A1M71 LRV 22



River VMI2057
WR71 / A1M71 LRV 22



Altro Walkway 20 in Fog at the Skou Building

| type + class | | ASTM F 1303 | flooring |
|--|---|---|----------------------------|
| Thickness and wear layer | | 2.0mm .08", homogenous construction | |
| Roll dimensions | | 6'7" x 65'5" 2m x 20m | |
| Weight | | 4.97 lbs./yd ² 2.6 kg/m ² 220 lbs. per roll | |
| Warranty | | 10 years | |
| Cleaning technology | | Altro Easyclean | |
| Static coefficient of friction | | ASTM D2047 | .78 dry, .8 wet |
| Dynamic coefficient of friction | | ANSI/NFSI B101.3 | .66 wet DCOF |
| Ramp test | | DIN 51130 | R10 |
| TRRL pendulum test | | BS 7976 ASTM E303 | 36+ |
| Static load limit | | ASTM F970 | 1000 psi |
| Indentation | | EN 433 | ≤ 0.10mm |
| Wear (abrasion) resistance | | EN 660 | ≤ 10% 50,000 cycles |
| Castor chair abrasion | | EN 425 | Pass |
| Flexibility | | ASTM F137 | Pass |
| Light fastness | | EN 20105-B02 | ≥ 6 |
| Sound insulation | | ISO 140-8 | 5dB |
| Electrical behaviors | | EN 1815 | ≤ 2kV Antistatic |
| Surface resistivity (only for Altro Walkway 20 SD) | | EN 1081 | 2x10 ⁷ Ω |
| Chemical resistance | | ASTM F925 | Tested |
| Fire and smoke performance | | CAN/ULC - S102.2 ASTM E648 ASTM E662 | Tested Class I < 450 |
| Minimum operating temperature | | -4°F (-20°C) | |
| VOC emissions | | CA 01350 FloorScore | Pass Certified |
| Bio-based content | | Manufactured with rapidly renewable bio-based content. | |
| Ortho-phthalate content | | Ortho-phthalate-free | |
| Recycled content | | Contains 10% pre-consumer + 10% post-consumer recycled content. | |
| Composition | Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability. | | |
| Backing | Non-woven polyester/cellulose glass fiber reinforcement scrim. | | |
| Installation and maintenance | Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altro.com , training clinic information at altro.com . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altro.com . Failure to install, heat weld, and/or maintain correctly could void the warranty. | | |
| Staining | Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation. | | |

LEED facts

LEED v4 This product may help contribute to the following credits

Altro Walkway 20 6

- Materials and resources
Contains recycled content **1**
- Materials and resources
Renewable bio-based content **1**
- Materials and resources - EPD
Environmental product declaration
Type III product specific **1**
- Materials and resources - HPD
Health product declaration **1**
- Environmental quality
Low emitting materials, flooring **1**
- Environmental quality
Low emitting materials, adhesives **1**


Discover more of our sustainability story and credentials at altro.com



Order samples 24 hours a day at altro.com and materialbank.com

These select quick-ship colors, are heavily stocked and consistently available in our North American warehouses.

Discover more online!



Maintenance guides




Illus. cleaning guides



Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries - www.altropics.com
- Solutions by area type - ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



USA 800 377 5597

CANADA 800 565 4658

support@altro.com

www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information.