

Wallgard

TECHNICAL DATA	STANDARD	WALLGARD
CLASSIFICATION		
Classification	EN 259-1	Homogeneous single layered vinyl flooring
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	1.3 mm
Total weight	EN ISO 23997	2100 g/m ²
Surface treatment		PU-Shield
Form of delivery	EN ISO 24341 Sheet (rolls)	Approx. 30 running metres x 200 cm Art. no. 21055 _ _ _ 3 digit colour number
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041	0019-0043-DoP-2013-07
Reaction to fire	EN ISO 13501-1 BS 476: Part 7 AS/NZS 3837 UNI 8457 ASTM E84	Class B-s2,d0 Class 1 Class B Class 1 Class B
TECHNICAL PERFORMANCES		
Wetroom test	GBR Class VT	Approved
Airborne particle emissions	EN 14644-1 ASTM F24 F51	ISO Class 4 Class A
Light fastness	EN ISO 105-B02	≥ level 7
Dimensional stability	EN ISO 23999	≤ 0.40%
Chemical resistance	EN ISO 26987	Excellent
Clean room test	ASTM F24/65 ASTM F51/00	Satisfactory Class A
Bacteria resistance	ISO 846 Part C	Does not favour growth
Seam strength	EN 684	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm
ENVIRONMENTAL PERFORMANCES		
Total VOC emissions	ISO 16000-9 AgBB/DIBt	≤ 10 µg/m ³ (after 28 days) Confirm
Outgassing VOC (23°C/90°C)	ISO-Acc _m class	≤ 9.6
COLOURS		
13		

The above information is subject to modification for the benefit of further improvement. (04/18). *For information - not binding.
According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

CUSTOMS TARIFF : 4820 5000 00

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Wallgard	NCS N°	Welding Rod No.	Wallgard	NCS N°	Welding Rod No.	Wallgard	NCS N°	Welding Rod No.	Wallgard	NCS N°	Welding Rod No.
220	S 0500-N	1290 011	224	S 0510-Y20R	1287 723	228	S 0530-Y10R	1287 725	232	S 4020-R80B	1287 724
221	S 1000-N	1288 125	225	S 0505-G30Y	1287 726	229	S 1020-G60Y	1287 721			
222	S 1002-Y50R	1287 728	226	S 1005-R90B	1288 157	230	S 1020-R90B	1287 727			
223	S 0804-Y30R	1287 729	227	S 0530-Y50R	1287 722	231	NCS S 4500-N	1287 730			

■ WESTERN EUROPE: Austria: Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 47 88 062 • Belgium: Tarkett Belux Sprl - Tel. +32 16 35 98 80 • Denmark: Tarkett A/S - Tel. +45 43 90 60 11 • Finland: Tarkett Oy - Tel. +358 9 4257 9000 • France: Tarkett SAS - Tel. +33 1 41 20 42 49 • Germany: Tarkett Holding GmbH, Bereich Objekt - Tel. +49 62 33 31 0 • Greece: Tarkett Monoprosopi Ltd - Tel. +30 210 5745 340 • Italy: Tarkett S.p.A. - Tel. +39 0744 7551 • Luxembourg: Tarkett CDL SA - Tel. +352 949 211 8804 • Netherlands: Tarkett Holding GmbH, Vestiging Nederland - Tel. +31 416 685 491 • Norway: Tarkett AS - Tel. +47 32 20 92 00 • Portugal: Tarkett SA - Tel. +351 21 427 64 20 • Spain: Tarkett Floors S.L. - Tel. +34 91 358 00 35 • Sweden: Tarkett Sverige AB - Tel. +46 771 25 10 00 • Switzerland: Tarkett Holding GmbH, Bereich Objekt Schweiz - Tel. +41 043 233 79 24 • Turkey: Tarkett Aspen - Tel. +90 212 213 65 80 • United Kingdom: Tarkett Ltd - Tel. +44 (0) 1622 854 040 ■ EASTERN EUROPE: Baltic Countries: Tarkett Baltics - Tel. +370 37 262 220 • Czech Republic: Tarkett org. slozka - Tel. +420 271 001 600 • Hungary: Tarkett Polska SP Z.O.O. magyarországi fioktelepe - Tel. +36 1 437 8150 • Poland: Tarkett Polska Sp. z o.o. - Tel. +48 22 16 09 231 • Russian Federation: ZAO Tarkett RUS - Tel. +7 495 775 3737 • Slovakia: Tarkett Polska, organizačná zložka - Tel. +421 2 48291 317 • South East Europe: Tarkett SEE - Tel. +381 21 7557 649 (44) 569 12 21 • Ukraine: Tarkett UA - Tel. +38 (0) 44 569 12 21 ■ ASIA AND OCEANIA: Australia: Tarkett Australia Pty Ltd - Tel. +61 2 88 53 12 00 • China: Tarkett Floor Covering (Shanghai) Co. Ltd. - Tel. +86 (21) 60 95 68 38 ext 841 • North East Asia: Tarkett Hong Kong Limited - Tel. +852 2511 8716 • India: Tarkett Flooring India Pvt. Ltd. - Bangalore - Tel. +91 80 4130 3793 - New Delhi - Tel. +91 11 4352 4073 - Mumbai - Tel. +91 22 2648 8750 • South East Asia: Tarkett Flooring Singapore Pte. Ltd. - Tel. +65 6346 1585 ■ AFRICA: Tarkett International: Tel. +33 1 41 20 41 01 ■ MIDDLE EAST: Tarkett Middle East: Tel. +961 1 51 3363/4 • Israel: Tarkett International: Tel. +33 1 41 20 41 01 ■ NORTH AMERICA: USA: Tarkett Inc. - Tel. +1 713 869 5811 / Johnsonite - Tel. +1 440 543 8916 • Canada: Tarkett Inc. - Tel. +1 450 293 173 ■ LATIN AMERICA: Brazil: Tarkett - Tel. 55 12 3954 7108 • Argentina - Chile - Uruguay: Tarkett Latam Mercosur - Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 • Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela: Tarkett - Tel. +55 11 9 8410 9310 / +55 11 95494 0069 • Mexico / Central America: Tarkett Latam Mexico - Tel. +55 11 98410 9310

Wallgard - 21055 0205 05 - 04/18

Printed on 100% recycled paper and cardboard - ♻️ recyclable



Wallgard

phthalate free
100%



WALL



ROLL

Wallgard

HOMOGENEOUS COMPACT VINYL

Functionality
and design for
demanding wall
applications

ANH NGOC THANH TRADING COMPANY LIMITED (ANTRADE CO., LTD.)

HCM office: R. 5.03, 5th FL., Phuong Tower, 31C Ly Tu Trong Str., Ben Nghe W., Dist. 1, HCMC. Tel: (+84) 28 38257622 / 28 38257623 Website: www.antrade.vn

HN office: R. 701, 7th FL., 131 Bui Thi Xuan Str., Hai Ba Trung District, Ha Noi City, Vietnam. Tel: (+84) 24 63289487 / 24 39749263 Hotline: +84 933 662138 Email: sales@antrade.vn



HOMOGENEOUS
COMPACT VINYL



Wallgard



DESIGN FLEXIBILITY

EXTENSIVE COLOUR OFFER IN SOFT, MODERN PATTERN

- Colours ranging from white to pastel tones for selection of varying shades within same collection.

CONTRAST COLOURS

- Colours which provide > 30% difference in luminance between sanitary-ware and wall covering for people with visual disabilities.

BEST IN CLASS FUNCTIONAL PERFORMANCE

SEALED AND SMOOTH SURFACE FOR OPTIMAL HYGIENE

- Impervious surface with PU-Shield for high resistance against stains and chemicals. Does not contribute to infection spreading.

IDEAL FOR SENSITIVE ENVIRONMENTS IN HEALTHCARE

- Reduces the level of environmental pollutants and guarantees a controlled level of contamination. Clean room approved.

ENHANCED PROTECTION AGAINST FIRE

- Classified B-s2,d0 in accordance to EN 13501-1.

PEOPLE FRIENDLY

IMPROVED INDOOR ENVIRONMENT AND AIR QUALITY

- Extremely low VOC emissions 100 times lower than the strictest standards in Europe.
- The phthalate-free plasticizers selected by Tarkett are approved for food contact containers and can be used for toys intended to be placed in the mouth by children.

EASY TO INSTALL

HORIZONTAL OR VERTICAL INSTALLATION

- Excellent hot welding seam strength.
- 2m width reducing the number of joints.

UNIQUE FLEXIBILITY FOR WATERTIGHT FINISH

- Approved for use in wetrooms.

WIDE RANGE OF ACCESSORIES TO PROVIDE THE PERFECT FINISH

- Flexible junction profile to reduce thickness difference between floor and wall covering for a perfect junction.

